

**AMENDMENTS TO THE CLAIMS:**

Kindly amend claims 1, 10 and 11, and add new claims 13-24 as shown below.

This listing of claims will replace all prior versions and listings of claims in the  
Application:

**Claim 1 (currently amended):** A method for manufacturing a liquid crystal display panel, the method comprising:

attaching a first substrate to a second substrate with a seal member and an auxiliary member to form said panel, said seal member forming an internal space and having an injection inlet for liquid crystal injection, said auxiliary member being arrayed around said seal member, wherein said seal member is formed with an air outlet forming member connected to said injection inlet, said air outlet forming member being extended toward a peripheral end of the panel, and said air outlet forming member is formed therein with an air outlet auxiliary member for forming an air outlet;

forming a cut line between said seal member and said auxiliary member;

cutting said panel along said cut line to traverse said air outlet forming member; and

injecting liquid crystal through said injection inlet

wherein said seal member, said auxiliary member and said air outlet are formed such that an unobstructed straight line air outlet path between said injection inlet and a peripheral of said liquid crystal display panel is created.

**Claim 2 (original):** The method as defined in claim 1, wherein said air outlet auxiliary member is positioned between the cut line and the peripheral end of the panel in order not to be cut when the panel is cut off.

HAYES SOLOWAY P.C.  
3450 E. SUNRISE DRIVE  
SUITE 140  
TUCSON, AZ 85718  
TEL. 520.882.7623  
FAX. 520.882.7643

175 CANAL STREET  
MANCHESTER, NH 03101  
TEL. 603.668.1400  
FAX. 603.668.8567

**Claim 3 (previously presented):** The method as defined in claim 1, wherein said air outlet forming member is aligned parallel to said air outlet auxiliary member in order to maintain constant a gap therebetween.

**Claim 4 (previously presented):** The method as defined in claim 1, wherein said air outlet auxiliary member and said air outlet forming member extend toward a peripheral end of said panel.

**Claim 5 (original):** The method as defined in claim 1, wherein said auxiliary member, said air outlet auxiliary member and said air outlet forming member formed at an external domain of the cut line, are all continuously formed as dashed lines.

**Claim 6 (original):** The method as defined in claim 1, wherein said seal member, said auxiliary member, said air outlet auxiliary member and said air outlet forming member are all simultaneously formed and made of the same material.

**Claim 7 (previously presented):** The method as defined in claim 3, wherein the gap between said air outlet auxiliary member and said air outlet forming member is 2 mm or more but not more than 7 mm.

**Claim 8 (previously presented):** The method as defined in claim 3, wherein the gap between said peripheral end of said panel and the distal ends of both said air outlet auxiliary member and said air outlet forming member is not more than 3 mm.

**Claim 9 (original):** The method as defined in claim 1, wherein there contains a plurality of said injection inlets and said air outlets.

**Claim 10 (currently amended):** A liquid crystal display panel manufactured by the method comprising:

HAYES SOLOWAY P.C.  
3450 E. SUNRISE DRIVE  
SUITE 140  
TUCSON, AZ 85718  
TEL. 520.882.7623  
FAX. 520.882.7643

175 CANAL STREET  
MANCHESTER, NH 03101  
TEL. 603.668.1400  
FAX. 603.668.8567

attaching a first substrate to a second substrate with a seal member and an auxiliary member to form said panel, said seal member forming an internal space and having an injection inlet for liquid crystal injection, said auxiliary member being arrayed around said seal member, wherein said seal member is formed with an air outlet forming member connected to said injection inlet, said air outlet forming member being extended toward a peripheral end of the panel, and said air outlet forming member is formed therein with an air outlet auxiliary member for forming an air outlet;

forming a cut line between said seal member and said auxiliary member;

cutting said panel along said cut line to traverse said air outlet forming member; and

injecting liquid crystal through said injection inlet

wherein said seal member, said auxiliary member and said air outlet are formed such that an unobstructed straight line air outlet path between said injection inlet and a peripheral of said liquid crystal display panel is created.

**Claim 11 (currently amended):** A method for manufacturing a liquid crystal display panel, the method comprising:

preparing a first substrate and a second substrate;

forming a seal member, an auxiliary member, and air outlet forming members on one of said substrates, wherein said seal member forms an internal space and has an injection inlet for liquid crystal injection, said auxiliary member is arrayed around said seal member, said air outlet forming members are formed with said auxiliary member and said air outlet forming members are connected to said injection inlet and extended toward a peripheral end of said panel;

attaching said first substrate to said second substrate with said seal member and said auxiliary member to form said panel;

positioning a cut line between said seal member and said auxiliary member;

cutting said panel along said cut line; and

injecting liquid crystal through said injection inlet

wherein said seal member, said auxiliary member and said air outlet are formed such that an unobstructed straight line air outlet path between said injection inlet and a peripheral of said liquid crystal display panel is created.

**Claim 12 (previously presented):** The method as defined in claim 11, wherein air outlet auxiliary members are further formed on one of said substrates within said air outlet forming members.

**Claim 13 (new):** A method for manufacturing a liquid crystal display panel, the method comprising:

attaching a first substrate to a second substrate with a seal member and an auxiliary member to form said panel, said seal member forming an internal space and having an injection inlet for liquid crystal injection, said auxiliary member being arrayed around said seal member, wherein said seal member is formed with an air outlet forming member connected to said injection inlet, said air outlet forming member being extended toward a peripheral end of the panel, and said air outlet forming member is formed therein with an air outlet auxiliary member for forming an air outlet;

forming a cut line between said seal member and said auxiliary member;

cutting said panel along said cut line to traverse said air outlet forming member; and

injecting liquid crystal through said injection inlet,

wherein said air outlet auxiliary member is positioned between the cut line and the peripheral end of the panel in order not to be cut when the panel is cut off.

**Claim 14 (new):** The method as defined in claim 13, wherein said air outlet forming member is aligned parallel to said air outlet auxiliary member in order to maintain constant a gap therebetween.

**Claim 15 (new):** The method as defined in claim 13, wherein said air outlet auxiliary member and said air outlet forming member extend toward a peripheral end of said panel.

**Claim 16 (new):** The method as defined in claim 13, wherein said seal member, said auxiliary member, said air outlet auxiliary member and said air outlet forming member are all simultaneously formed and made of the same material.

**Claim 17 (new):** The method as defined in claim 13, wherein there contains a plurality of said injection inlets and said air outlets.

**Claim 18 (new):** A method for manufacturing a liquid crystal display panel, the method comprising:

attaching a first substrate to a second substrate with a seal member and an auxiliary member to form said panel, said seal member forming an internal space and having an injection inlet for liquid crystal injection, said auxiliary member being arrayed around said seal member, wherein said seal member is formed with an air outlet forming member connected to said injection inlet, said air outlet forming member being extended toward a peripheral end of the panel, and said air outlet forming member is formed therein with an air outlet auxiliary member for forming an air outlet;

forming a cut line between said seal member and said auxiliary member;  
cutting said panel along said cut line to traverse said air outlet forming member; and  
injecting liquid crystal through said injection inlet,  
wherein said auxiliary member, said air outlet auxiliary member and said air outlet forming member formed at an external domain of the cut line, are all continuously formed as dashed lines.

**Claim 19 (new):** The method as defined in claim 18, wherein said air outlet forming member is aligned parallel to said air outlet auxiliary member in order to maintain constant a gap therebetween.

**Claim 20 (new):** The method as defined in claim 18, wherein said air outlet auxiliary member and said air outlet forming member extend toward a peripheral end of said panel.

**Claim 21 (new):** The method as defined in claim 18, wherein said seal member, said auxiliary member, said air outlet auxiliary member and said air outlet forming member are all simultaneously formed and made of the same material.

**Claim 22 (new):** The method as defined in claim 18, wherein there contains a plurality of said injection inlets and said air outlets.

**Claim 23 (new):** A method for manufacturing a liquid crystal display panel, the method comprising:

attaching a first substrate to a second substrate with a seal member and an auxiliary member to form said panel, said seal member forming an internal space and having an injection inlet for liquid crystal injection, said auxiliary member being arrayed around said seal member, wherein said seal member is formed with an air outlet forming member connected to said

injection inlet, said air outlet forming member being extended toward a peripheral end of the panel, and said air outlet forming member is formed therein with an air outlet auxiliary member for forming an air outlet;

forming a cut line between said seal member and said auxiliary member;

cutting said panel along said cut line to traverse said air outlet forming member; and

injecting liquid crystal through said injection inlet,

wherein said air outlet forming member is aligned parallel to said air outlet auxiliary member in order to maintain constant a gap therebetween, and

the gap between said air outlet auxiliary member and said air outlet forming member is 2 mm or more but not more than 7 mm.

**Claim 24 (new):** A method for manufacturing a liquid crystal display panel, the method comprising:

attaching a first substrate to a second substrate with a seal member and an auxiliary member to form said panel, said seal member forming an internal space and having an injection inlet for liquid crystal injection, said auxiliary member being arrayed around said seal member, wherein said seal member is formed with an air outlet forming member connected to said injection inlet, said air outlet forming member being extended toward a peripheral end of the panel, and said air outlet forming member is formed therein with an air outlet auxiliary member for forming an air outlet;

forming a cut line between said seal member and said auxiliary member;

cutting said panel along said cut line to traverse said air outlet forming member; and

injecting liquid crystal through said injection inlet,

wherein said air outlet forming member is aligned parallel to said air outlet auxiliary member in order to maintain constant a gap therebetween, and

the gap between said peripheral end of said panel and the distal ends of both said air outlet auxiliary member and said air outlet forming member is not more than 3 mm.

**HAYES SOLOWAY P.C.**  
3450 E. SUNRISE DRIVE  
SUITE 140  
TUCSON, AZ 85718  
TEL. 520.882.7623  
FAX. 520.882.7643

175 CANAL STREET  
MANCHESTER, NH 03101  
TEL. 603.668.1400  
FAX. 603.668.8567